

according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Version: Replaces version: 8.0 Language: en-GB Date of print: 4/12/2023

Revision date: 30/11/2023

Refrifluid 1

Material number E701240x

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Refrifluid 1 Trade name:

This safety data sheet pertains to the following products:

E7012402: 25 L E7012404: 50 L E7012406: 100 L

KD10-80TF-400K-EJQ6

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Heat transfer fluids.

Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Lauda Dr. R. Wobser GmbH & Co. KG

Street/POB-No.: Laudaplatz 1

Postal Code, city: 97922 Lauda-Königshofen

Germany www.lauda.de info@lauda.de +49 (0)9343-503-0 Telefax: +49 (0)9343-503-222

Department responsible for information

www:

E-mail:

Department Quality Management,

Telephone: +49 9343 503-331, e-mail info@lauda.de

1.4 Emergency telephone number

National Poisons Information Service (Birmingham Unit)

Telephone: 844 892 0111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Repr. 1B; H360 May damage fertility or the unborn child.

STOT RE 2; H373 May cause damage to organs through prolonged or repeated exposure.

2.2 Label elements

Labelling (CLP)



Signal word: Danger

Hazard statements: H360 May damage fertility or the unborn child.

> H373 May cause damage to organs through prolonged or repeated exposure.



according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Revision date: 30/11/2023
Version: 9.0
Replaces version: 8.0
Language: en-GB
Date of print: 4/12/2023

Refrifluid 1

Material number E701240x Page: 2 of 1º

Precautionary statements: P201 Obtain special instructions before use.

P260 Do not breathe mist/vapours.

P280 Wear protective gloves/protective clothing/eye protection.
P308+P313 IF exposed or concerned: Get medical advice/attention.

P501 Dispose of contents/container to hazardous or special waste collection point.

Special labelling

Text for labelling: Contains: ethylene glycol, Sodium 2-ethylhexanoate

Restricted to professional users.

2.3 Other hazards

Further hazardous properties cannot be excluded.

Endocrine disrupting properties, Results of PBT and vPvB assessment:

This product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% (w/w) or higher.

The product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Hazardous ingredients:

Identifiers	Designation Classification	Content
REACH 01-2119456816-28-xxxx EC No. 203-473-3 CAS 107-21-1	Ethylene glycol Acute Tox. 4; H302. STOT RE 2; H373.	10 - 25 %
EC No. 243-283-8 CAS 19766-89-3	Sodium 2-ethylhexanoate Repr. 1B; H360D.	< 1 %

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: First aider: Pay attention to self-protection! If medical advice is needed, have product container or label

at hand.

In case of inhalation: Remove person to fresh air and keep comfortable for breathing. Consult physician.

Following skin contact: After contact with skin, wash immediately with soap and plenty of water. Take off contaminated clothing

and wash it before reuse. In the event of discomfort seek medical treatment.

After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove

contact lenses, if present and easy to do. Continue rinsing. Subsequently consult an ophthalmologist.

After swallowing: Rinse mouth and drink large quantities of water. Do not induce vomiting. Consult physician. Never give

anything by mouth to an unconscious person.



according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Version: 9.0
Replaces version: 8.0
Language: en-GB
Date of print: 4/12/2023

Revision date: 30/11/2023

Refrifluid 1

Material number E701240x Page: 3 of 1

4.2 Most important symptoms and effects, both acute and delayed

May cause damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: Product is non-combustible. Extinguishing is to be in accordance with the surrounding fire.

Water spray jet, foam, extinguishing powder, carbon dioxide

Extinguishing media which must not be used for safety reasons:

Full water jet

5.2 Special hazards arising from the substance or mixture

Fires in the immediate vicinity may cause the development of dangerous vapours.

In the event of a fire, the following may be produced when the water evaporates: carbon monoxide and

carbon dioxide

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information: Hazchem-Code: -

Cool endangered containers with water jetspray. Do not allow fire water to penetrate into surface or

ground water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid exposure. Seal off endangered area. Keep unprotected people away. Provide good ventilation. Avoid contact with the substance. Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse.

6.2 Environmental precautions

Do not allow to penetrate into soil, waterbodies or drains.

6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents) and place in closed containers for disposal. Thoroughly clean surrounding area.

6.4 Reference to other sections

Refer additionally to section 8 and 13.



according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Revision date: 30/11/2023
Version: 9.0
Replaces version: 8.0
Language: en-GB
Date of print: 4/12/2023

Refrifluid 1

Material number E701240x Page: 4 of 10

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling: Obtain special instructions before use. Provide adequate ventilation, and local exhaust as needed. Avoid

contact with the substance. Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse. Safety shower and eye wash station should be easily accessible to the work area.

Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.

Precautions against fire and explosion:

Avoid unenclosed light, fire and other ignition sources.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Keep containers in a dry, well-ventilated and cool place. Protect from heat and direct sunlight. Store only

in original container. Store carefully closed containers upright to prevent any leaks.

storage temperature: 5 - 35 °C

Shelf life: 24 months

Hints on joint storage: Keep away from food, drink and animal feedingstuffs.

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Туре	Limit value
107-21-1	Ethylene glycol	Great Britain: WEL-STEL	104 mg/m³; 40 ppm
			(vapour, may be absorbed through the skin)
		Great Britain: WEL-TWA	10 mg/m³ (may be absorbed through the skin)
		Great Britain: WEL-TWA	52 mg/m ³ ; 20 ppm
			(vapour, may be absorbed through the skin)

DNEL/DMEL: Information about Ethylene glycol:

DNEL long-term, workers, inhalative, local: 35 mg/m³ DNEL long-term, workers, dermal, systemic: 106 mg/kg bw/d DNEL long-term, consumers, inhalative, local: 7 mg/m³ DNEL long-term, consumers, dermal, systemic: 53 mg/kg bw/d

Information about Sodium 2-ethylhexanoate:

DNEL long-term, workers, inhalative, systemic: 14 mg/m³ DNEL long-term, workers, dermal, systemic: 2 mg/kg bw/d DNEL long-term, consumers, inhalative, systemic: 3.5 mg/m³ DNEL long-term, consumers, dermal, systemic: 1 mg/kg bw/d DNEL long-term, consumers, oral, systemic: 1 mg/kg bw/d



according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Revision date: 30/11/2023
Version: 9.0
Replaces version: 8.0
Language: en-GB
Date of print: 4/12/2023

Refrifluid 1

Material number E701240x Page: 5 of 1

PNEC: Information about ethylene glycol:

PNEC water (freshwater): 10 mg/L
PNEC water (marine water): 1 mg/L
PNEC water (intermittent release): 10 mg/L
PNEC sediment (freshwater): 37 mg/kg dw
PNEC sediment (marine water): 3.7 mg/kg dw

PNEC soil: 1.53 mg/kg dw

PNEC sewage treatment plant stp: 199.5 mg/L Information about Sodium 2-ethylhexanoate: PNEC water (freshwater): 0.36 mg/L PNEC water (marine water): 0.036 mg/L PNEC water (intermittent release): 0.493 mg/L PNEC sediment (freshwater): 0.301 mg/kg dw PNEC sediment (marine water): 0.0301 mg/kg dw

PNEC soil: 0.0579 mg/kg dw

PNEC sewage treatment plant stp: 71.7 mg/L

8.2 Exposure controls

Provide adequate ventilation, and local exhaust as needed.

Personal protection equipment

Occupational exposure controls

Respiratory protection: Respiratory protection must be worn whenever the WEL levels have been exceeded.

Use filter type A (= against vapours of organic substances) according to BS EN 14387. The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product.

Hand protection: Protective gloves according to BS EN 374.

Glove material: Nitrile rubber Breakthrough time: >480 min.

Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection: Tightly sealed goggles according to BS EN ISO 16321-1:2022.

Body protection: Wear suitable protective clothing.

General protection and hygiene measures:

Obtain special instructions before use. Avoid contact with the substance. Wash hands before breaks and immediately after handling the product. When using do not eat, drink or smoke. Work place should be equipped with a shower and an eye rinsing apparatus. Take off contaminated clothing and wash it before

reuse.

Environmental exposure controls

Refer to "6.2 Environmental precautions".

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: Physical state at 20 °C and 101.3 kPa: liquid

Colour: transparent, pink

Odour: characteristic
Odour threshold: No data available

pH: at 20 °C: 6 - 8



according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Revision date: 30/11/2023
Version: 9.0
Replaces version: 8.0
Language: en-GB
Date of print: 4/12/2023

Refrifluid 1

Material number E701240x Page: 6 of 1º

Melting point/freezing point:

No data available

Initial boiling point and boiling range: 109 $^{\circ}$ C Flash point/flash point range: > 60 $^{\circ}$ C

Evaporation rate: No data available Flammability: No data available

Explosion limits: LEL (Lower Explosion Limit): 3.20 Vol-%

UEL (Upper Explosive Limit): 15.30 Vol-%

Vapour pressure: at 20 °C: 22.23 hPa

at 50 °C: 117.16 hPa No data available

Vapour density: No data available
Density: at 20 °C: 1.045 g/mL

Water solubility: at 20 °C: completely miscible

Partition coefficient: n-octanol/water: No data available

Auto-ignition temperature: 400 °C

Decomposition temperature:

No data available

viscosity, dynamic:

at 20 °C: 1.22 mPa*s

viscosity, kinematic:

at 20 °C: 1.17 mm²/s

Explosive properties:

No data available

Oxidizing characteristics:

No data available

9.2 Other information

Additional information: No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Refer to subsection "Possilbility of hazardous reactions".

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4 Conditions to avoid

Protect against heat /sun rays. Avoid unenclosed light, fire and other ignition sources.

10.5 Incompatible materials

Oxidizing agents, rust

10.6 Hazardous decomposition products

In case of fire may be liberated: carbon monoxide and carbon dioxide

Thermal decomposition: No data available



according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Revision date: 30/11/2023
Version: 9.0
Replaces version: 8.0
Language: en-GB
Date of print: 4/12/2023

Refrifluid 1

Material number E701240x Page: 7 of

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is

available for the product as such.

Acute toxicity (oral): Based on available data, the classification criteria are not met.

ATEmix calculated: > 2000 mg/kg

Acute toxicity (dermal): Based on available data, the classification criteria are not met.

ATEmix calculated: > 2000 mg/kg

Acute toxicity (inhalative): Based on available data, the classification criteria are not met.

ATEmix calculated: > 20 mg/L

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/irritation: Based on available data, the classification criteria are not met.

Sensitisation to the respiratory tract: Based on available data, the classification criteria are not met.

Skin sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Repr. 1B; H360 = May damage fertility or the unborn child.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Based on available data, the classification criteria are not

met.

Specific target organ toxicity (repeated exposure): STOT RE 2; H373 = May cause damage to organs through

prolonged or repeated exposure.

Aspiration hazard: Based on available data, the classification criteria are not met.

Other information: Information about ethylene glycol:

LD50 Rat, oral: 7712 mg/kg (OECD 401) LD50 Mouse, dermal: > 3500 mg/kg (OECD 402) LD50 Rat, inhalative (Aerosol): 2.5 mg/L/6h

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Information about ethylene glycol

Algae toxicity:

EC50 Pseudokirchneriella subcapitata (green algae): 6500 - 13000 mg/L/96h (EPA 600/9-78-018, 1978)

Daphnia toxicity:

EC50: >100 mg/L/48h (OECD 202)

Fish toxicity:

Short-term, LC50 Pimephales promelas (fathead minnow): 72860 mg/L/96h (EPA 600/4-90/027.U.S.) Long-term, NOEC Pimephales promelas (fathead minnow): 15380 mg/L/7d (EPA 600/4-90/027.U.S.)

12.2 Persistence and degradability

Further details: No data available

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water:

No data available



according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Refrifluid 1

Material number E701240x Page: 8 of

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

The product does not contain any substances classified as PBT or vPvB.

12.6 Other adverse effects

General information: Do not allow to penetrate into soil, waterbodies or drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number: 16 01 14* = antifreeze fluids containing hazardous substances

* = Evidence for disposal must be provided.

Recommendation: Dispose of waste according to applicable legislation.

Package

Recommendation: Dispose of waste according to applicable legislation. Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number

ADR/RID, IMDG, IATA-DGR: not applicable

14.2 UN proper shipping name

ADR/RID, IMDG, IATA-DGR: Not restricted

14.3 Transport hazard class(es)

ADR/RID, IMDG, IATA-DGR: not applicable

14.4 Packing group

ADR/RID, IMDG, IATA-DGR: not applicable

14.5 Environmental hazards

Marine pollutant: no

14.6 Special precautions for user

No dangerous good in sense of these transport regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No data available



according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Revision date: 30/11/2023 Version: 9.0 Replaces version: 8.0 Language: en-GB Date of print: 4/12/2023

Refrifluid 1

Material number E701240x

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations - Great Britain

Hazchem-Code:

No data available

National regulations - EC member states

Further regulations, limitations and legal requirements:

Use restriction according to REACH annex XVII, no.: 3, 30, 75

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

SECTION 16: Other information

Further information

Wording of the H-phrases under paragraph 2 and 3:

H302 = Harmful if swallowed.

H360 = May damage fertility or the unborn child.

H360D = May damage the unborn child.

H373 = May cause damage to organs through prolonged or repeated exposure.

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

AS/NZS: Australian Standards/New Zealand Standards

CAS: Chemical Abstracts Service CFR: Code of Federal Regulations

CLP: Classification, Labelling and Packaging DMEL: Derived minimal effect level DNEL: Derived no-effect level

EC: European Community EC50: Effective Concentration 50%

EN: European Standard

EQ: Excepted quantities

IATA: International Air Transport Association

IATA-DGR: Interna@nal Air Transport Associa@n – Dangerous Goods Regula@ns

IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

IMDG Code: International Maritime Dangerous Goods Code

LC50: Median lethal concentration LD50: Lethal dose 50%

LEL: Lower Explosion Limit

MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OEL: Occupational Exposure Limit Value

OSHA: Occupational Safety and Health Administration PBT: Persistent, bioaccumulative and toxic

PNEC: Predicted no-effect concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

Repr.: Reproductive toxicity

RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail

STOT RE: Specific target organ toxicity - repeated exposure

TLV: Threshold Limit Value

TRGS: Technical Rules for Hazardous Substances

vPvB: Very persistent and very bioaccumulative

WEL: Workplace Exposure Limit



according to Regulation (EC) No 1907/2006, as retained and amended in UK law [UK REACH]

Revision date: 30/11/2023
Version: 9.0
Replaces version: 8.0
Language: en-GB
Date of print: 4/12/2023

Refrifluid 1

Material number E701240x Page: 10 of 10

Reason of change: Changes in section 2: Classification, labelling

Changes in section 3: Composition/information on ingredients

Changes in section 7: Storage class

Changes in section 15: National regulations

General revision

Date of first version: 28/11/2012

Department issuing data sheet

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.